$RHYTHM^{TM}$





Rhythm shown with Pearl shell



Rhythm shown with Pearl shell / Coastal Grey cabinet and Polymer step

Seating Capacity	7 adults
Dimensions	213 x 213 x 93.5 cm
Water Capacity	1,350 liters
Weight	380 kg dry; 2,290 kg filled*
Spa Shell Options	Pearl, Sterling Marble, Tuscan Sun or Desert
Cabinet Options	Coastal Grey, Espresso, Teak
Jets - 35 (all with stainless steel trim)	5 Directional Hydromassage jets
	3 Rotary Hydromassage jets
	27 Directional Precision™ jets
Waterfall	Included
Jet Pump 1	Wavemaster [™] 8200; Two-speed, 2.0 HP Continuous Duty, 4.0 HP Breakdown Torque
Jet Pump 2	Wavemaster 8000; One-speed, 2.0 HP Continuous Duty, 4.0 HP Breakdown Torque
Water Care System	Frog [™] In-Line Cartridge Ready
Ozone System (Optional)	FreshWater® III Corona Discharge
Control System	IQ 2020™ 230v/16 amp, 50 Hz
Control System Lighting	IQ 2020 [™] 230v/16 amp, 50 Hz 10 multi-colour LED points of light, dimmable
	· · · · · · · · · · · · · · · · · · ·
Lighting	10 multi-colour LED points of light, dimmable
Lighting Heater	10 multi-colour LED points of light, dimmable No-Fault™ 2000w/230v FiberCor® Insulation; Certified to the APSP 14 National Standard and the California Energy Com-
Lighting Heater Energy Efficiency	10 multi-colour LED points of light, dimmable No-Fault™ 2000w/230v FiberCor® Insulation; Certified to the APSP 14 National Standard and the California Energy Commission (CEC) in accordance with California law
Lighting Heater Energy Efficiency Effective Filtration Area	10 multi-colour LED points of light, dimmable No-Fault™ 2000w/230v FiberCor® Insulation; Certified to the APSP 14 National Standard and the California Energy Commission (CEC) in accordance with California law 6 m² top loading
Lighting Heater Energy Efficiency Effective Filtration Area	10 multi-colour LED points of light, dimmable No-Fault™ 2000w/230v FiberCor® Insulation; Certified to the APSP 14 National Standard and the California Energy Commission (CEC) in accordance with California law 6 m² top loading 9 to 6.5 cm tapered, 24 kg/m³ density foam core
Lighting Heater Energy Efficiency Effective Filtration Area Vinyl Cover	10 multi-colour LED points of light, dimmable No-Fault™ 2000w/230v FiberCor® Insulation; Certified to the APSP 14 National Standard and the California Energy Commission (CEC) in accordance with California law 6 m² top loading 9 to 6.5 cm tapered, 24 kg/m³ density foam core Ash, Chestnut or Caramel CoverCradle™, CoverCradle II, Lift 'n Glide™ or
Lighting Heater Energy Efficiency Effective Filtration Area Vinyl Cover Cover Lifter (Optional)	10 multi-colour LED points of light, dimmable No-Fault™ 2000w/230v FiberCor® Insulation; Certified to the APSP 14 National Standard and the California Energy Commission (CEC) in accordance with California law 6 m² top loading 9 to 6.5 cm tapered, 24 kg/m³ density foam core Ash, Chestnut or Caramel CoverCradle™, CoverCradle II, Lift 'n Glide™ or UpRite™

 $^{^{\}star}$ Includes water and 7 adults weighing 80 kg each

From the makers of

