TEMPOTM





Tempo shown with Tuscan Sun shell



Tempo shown with Tuscan Sun shell / Espresso cabinet and Everwood step

Seating Capacity	6 adults
Dimensions	226 x 226 x 99 cm
Water Capacity	1,575 litres
Weight	415 kg dry; 2,470 kg filled*
Spa Shell Options	Pearl, Sterling Marble, Tuscan Sun or Desert
Cabinet Options	Coastal Grey, Espresso, Teak
Jets - 45 (all with stainless steel trim)	6 Directional Hydromassage jets
	4 Rotary Hydromassage jets
	35 Directional Precision [™] jets
Waterfall	Included
Jet Pump 1	Wavemaster™ 9200; Two-speed, 2.5 HP Continuous Duty, 5.2 HP Breakdown Torque
Jet Pump 2	Wavemaster 9000; One-speed, 2.5 HP Continuous Duty, 5.2 HP Breakdown Torque
Water Care System	Frog [™] In-Line Cartridge Ready
Ozone System (Optional)	FreshWater® III Corona Discharge
Ozone System (Optional) Control System	FreshWater [®] III Corona Discharge IQ 2020™ 230v/20 A, 50 Hz
Control System	IQ 2020™ 230v/20 A, 50 Hz
Control System Lighting	IQ 2020™ 230v/20 A, 50 Hz 10 multi-colour LED points of light, dimmable
Control System Lighting Heater	IQ 2020™ 230v/20 A, 50 Hz 10 multi-colour LED points of light, dimmable No-Fault™ 2000w/230v FiberCor® Insulation; Certified to the APSP 14 National Standard and the California Energy Commission (CEC) in accordance with California
Control System Lighting Heater Energy Efficiency	IQ 2020 [™] 230v/20 A, 50 Hz 10 multi-colour LED points of light, dimmable No-Fault [™] 2000w/230v FiberCor [®] Insulation; Certified to the APSP 14 National Standard and the California Energy Commission (CEC) in accordance with California law
Control System Lighting Heater Energy Efficiency Effective Filtration Area	IQ 2020™ 230v/20 A, 50 Hz 10 multi-colour LED points of light, dimmable No-Fault™ 2000w/230v FiberCor® Insulation; Certified to the APSP 14 National Standard and the California Energy Commission (CEC) in accordance with California law 6m², top loading 9 to 6.5 cm tapered, 32 kg/m³ density foam core
Control System Lighting Heater Energy Efficiency Effective Filtration Area Vinyl Cover	IQ 2020 [™] 230v/20 A, 50 Hz 10 multi-colour LED points of light, dimmable No-Fault [™] 2000w/230v FiberCor [®] Insulation; Certified to the APSP 14 National Standard and the California Energy Commission (CEC) in accordance with California law 6m², top loading 9 to 6.5 cm tapered, 32 kg/m³ density foam core Ash, Chestnut or Caramel CoverCradle [™] , CoverCradle II, Lift 'n Glide [™] or

 $^{^{\}star}$ Includes water and 6 adults weighing 80 kg each.

From the makers of

